

Residential VIP Specification Sheet

Residential VIP Overview:

The VP410-R is the communication HUB for the Residential PipeBurst Pro system. It communicates with all wireless devices.

The VIP integrates with ionleaks.com, PipeBurst Pro's proprietary monitoring and control software.

Residential VIP Specifications:

- Part #: VP410-R
- Dimensions: 6-3/4" W x 5-1/2" H x 5" D
- Power Source: AC power adaptor
- Voltage: 5 VDC standard or optional 15 VDC
- Housing: Black Nylon Plastic
- Audible Notifications: Internal speaker
- Visual Notifications: Five bi-color LED lights (green/red)
- Wireless Frequency: 915 MHz
- Wireless Device Capacity: 2 Zones, 20 Devices
- (2) Expandable card slots for input/output/relay controls



VP410-R

*Wireless range dependent on environmental factors including but not limited to building materials.

Residential VIP Features

- With the instructional label displayed on the front panel, never search for the manual.
- Easy wireless device setup with one button sync.
- Installing extra wireless devices is quick and easy.
- Communicates with up to 20 serialized wireless devices providing expansive coverage.
- Comprehensive system monitoring and control with app.ionleaks.com via any internet capable device. (VIP includes an Ethernet port for standard connection)



800.246.LEAK (5325)
info@pipeburstpro.com

©2020 GreenField Direct, LLC

